

# **PENNZOIL PLATINUM™ AXLE SAE 75W-140** *Long*

*Service Life, Wide Temperature Use Gear Oil*

## **TECHNICAL DATA SHEET**



PENNZOIL PLATINUM™ AXLE SAE 75W-140, combines a premium performance gear oil additive package with a high quality synthetic base stock. The result is a gear oil that provides excellent low temperature fluidity for safe lubrication during very low temperature axle and transmission startup, and also maintains a thick protective oil film during extremely hot operating conditions.

PENNZOIL PLATINUM™ AXLE SAE 75W-140 is formulated with all the performance additives necessary for outstanding protection of gears and bearings. It contains extreme pressure agents which protect against shock loading and wear. Foam inhibitors protect against oil aeration, which can rupture the lubricant film and cause wear due to lack of lubrication. Special rust inhibitors are incorporated into PENNZOIL PLATINUM™ AXLE SAE 75W-140 to protect against corrosion that can result from condensation. Oxidation inhibitors are included to further enhance this synthetic oil's inherent oxidation stability, resulting in a lubricant with exceptionally long service life and excellent resistance to deposit and sludge formation during high temperature operation.

### **PERFORMANCE, FEATURES & BENEFITS**

- Maintains fluidity at low temperatures
- Does not thin out at high temperatures
- Long service life
- Prevents rust
- Resists oxidation
- Withstands heavy shock loads
- High viscosity index

### **MAIN APPLICATIONS**



PENNZOIL PLATINUM™ AXLE SAE 75W-140 is designed primarily for the lubrication of differentials and manual transmissions requiring an API GL-5 gear lubricant. It can be used in passenger cars, light trucks, sport utility vehicles and vans. It continues to flow at very low temperatures, providing especially good protection of gears and bearings in extreme cold weather. It also provides excellent service in hot climates by not thinning at high temperatures, thereby maintaining a full film of protective lubricant on gear teeth. In hot running gear boxes, it allows long service due to the excellent stability of the synthetic base stocks used in it.

# **PENNZOIL PLATINUM™ AXLE SAE 75W-140** *Long Service Life, Wide Temperature Use Gear Oil*

## Limited Slip Capability

PENNZOIL PLATINUM™ AXLE SAE 75W-140 is suitable for use in conventional axles and a number of older and moderately loaded limited slip differentials. Some limited slip differentials may require additional limited slip additive due to the mechanical set up of individual vehicles. When the vehicle manufacturer requires more than 2-3% (2 ounces in a 2 quart (64 ounces) differential) of limited slip additive (limited slip friction modifier), additional limited slip additive should be used. These may include some 2000 and later Ford pick-up trucks (requires 6-7%) in ¾ and 1 ton trucks with limited slip differentials. Some Dodge trucks using MS-8985 SAE 75W-140 axle fluid require addition of limited slip additive for a total of 5%. In these cases, it is recommended to follow the vehicle manufacturer's recommendation for addition of limited slip additive added to prevent chattering in certain manouvres. Follow OEM requirements and check specific requirements for the vehicles differential. Requirements may vary within a vehicle model and model year as different differentials are used in various engine and transmission combinations or with specific vehicle options.

## TYPICAL PHYSICAL CHARACTERISTICS

| Properties           |            | Method     | PENNZOIL PLATINUM™<br>AXLE SAE 75W-140 |
|----------------------|------------|------------|----------------------------------------|
| Gravity, Specific    | @60°F      | ASTM D1298 | 0.865                                  |
| Pounds per Gallon    |            |            | 7.3                                    |
| Flash Point          | °C(°F)     | ASTM D92   | 188(370)                               |
| Pour Point           | °C(°F)     | ASTM D97   | -45(-49)                               |
| Kinematic Viscosity  | @40°C cSt  | ASTM D445  | 175                                    |
| Kinematic Viscosity  | @100°C cSt | ASTM D445  | 24.6                                   |
| Viscosity Index      |            | ASTM D2270 | 173                                    |
| Brookfield Viscosity | @-40°C cP  | ASTM D2983 | 126 000                                |

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

## SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

PENNZOIL PLATINUM™ AXLE SAE 75W-140 meets all the requirements of API Service Classification GL-5 and SAE J2360.

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

To find the right Pennzoil® product for your vehicles and equipment, please consult [www.pennzoil.com](http://www.pennzoil.com) to look up the right motor oil recommendation using our oil selector.

# **PENNZOIL PLATINUM™ AXLE SAE 75W-140** *Long Service Life, Wide Temperature Use Gear Oil*

## **HEALTH, SAFETY & ENVIRONMENT**

### **Health and Safety**

Pennzoil Platinum™ Axle 75W-140 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from [www.epc.shell.com](http://www.epc.shell.com)

### **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## **ADDITIONAL INFORMATION**

### **Advice**

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Help Desk.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 09.06.2020          |
| 1.4     | 01.04.2020     | 800010016439 | Date of last issue: 18.12.2019  |
|         |                |              | Date of first issue: 16.02.2015 |

### SECTION 1. IDENTIFICATION

Product name : Pennzoil Platinum Axle 75W-140

Product code : 001F1399

#### Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Canada Products**  
400 - 4th Avenue S.W  
Calgary AB T2P 0J4  
Canada

Telephone : (+1) 8006611600

Telefax : (+1) 4033848345

Emergency telephone number : CHEMTREC (24 hr): 1 (703) 527-3887 or 1 (800) 424-9300 (US)  
CANUTEC (24 hr): (+1) 613-996-6666; Toll Free: 1-888-CAN-UTEC (226-8832)

#### Recommended use of the chemical and restrictions on use

Recommended use : Transmission oil.  
Research and development product.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

#### GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:  
Not classified as a physical hazard under GHS criteria.  
HEALTH HAZARDS:  
Not classified as a health hazard under GHS criteria.  
ENVIRONMENTAL HAZARDS:  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**  
No precautionary phrases.  
**Response:**

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

No precautionary phrases.

**Storage:**

No precautionary phrases.

**Disposal:**

No precautionary phrases.

**Other hazards which do not result in classification**

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

|                 |                                                                                                                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Substance name  | : Pennzoil Platinum Axle 75W-140                                                                                                                                                                                                 |
| Chemical nature | : Synthetic base oil and additives.<br>Highly refined mineral oil.<br>The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.<br>The highly refined mineral oil is only present as additive diluent. |

**Hazardous components**

| Chemical name                                                                | CAS-No.     | Concentration (% w/w) |
|------------------------------------------------------------------------------|-------------|-----------------------|
| Polyolefin                                                                   | 68649-11-6  | < 20                  |
| Distillates (Fischer - Tropsch), heavy, C18-50 – branched, cyclic and linear | 848301-69-9 | < 30                  |
| Distillates (petroleum), hydrotreated light                                  | 64742-47-8  | < 3                   |
| Alkyl amine                                                                  | 68955-53-3  | 0.1 - 0.99            |
| Alkenyl amine                                                                | 112-90-3    | 0.1 - 0.99            |
| Alcohols, C12-14, ethoxylated                                                | 68439-50-9  | 0.1 - 0.3             |

### SECTION 4. FIRST-AID MEASURES

|                         |                                                                                                                                                                                    |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| If inhaled              | : No treatment necessary under normal conditions of use.<br>If symptoms persist, obtain medical advice.                                                                            |
| In case of skin contact | : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.<br>If persistent irritation occurs, obtain medical attention.          |
| In case of eye contact  | : Flush eye with copious quantities of water.<br>Remove contact lenses, if present and easy to do. Continue rinsing.<br>If persistent irritation occurs, obtain medical attention. |
| If swallowed            | : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.                                                                         |

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoi Platinum Axle 75W-140

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 09.06.2020          |
| 1.4     | 01.04.2020     | 800010016439 | Date of last issue: 18.12.2019  |
|         |                |              | Date of first issue: 16.02.2015 |

---

|                                                             |                                                                                                                                                                                       |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Most important symptoms and effects, both acute and delayed | : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. |
| Protection of first-aiders                                  | : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.                         |
| Notes to physician                                          | : Treat symptomatically.                                                                                                                                                              |

---

### SECTION 5. FIRE-FIGHTING MEASURES

|                                               |                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                  | : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.                                                                                                                                                                                                                                           |
| Unsuitable extinguishing media                | : Do not use water in a jet.                                                                                                                                                                                                                                                                                                                               |
| Specific hazards during fire-fighting         | : Hazardous combustion products may include:<br>A complex mixture of airborne solid and liquid particulates and gases (smoke).<br>Carbon monoxide may be evolved if incomplete combustion occurs.<br>Unidentified organic and inorganic compounds.                                                                                                         |
| Specific extinguishing methods                | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                                                                                                                                                                  |
| Special protective equipment for firefighters | : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469). |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

|                                                                     |                                                                                                                                                                                                                                                                                |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Avoid contact with skin and eyes.                                                                                                                                                                                                                                            |
| Environmental precautions                                           | : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.<br><br>Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for                                           | : Slippery when spilt. Avoid accidents, clean up immediately.                                                                                                                                                                                                                  |

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 09.06.2020          |
| 1.4     | 01.04.2020     | 800010016439 | Date of last issue: 18.12.2019  |
|         |                |              | Date of first issue: 16.02.2015 |

---

|                             |                                                                                                                                                                                                                                                       |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| containment and cleaning up | Prevent from spreading by making a barrier with sand, earth or other containment material.<br>Reclaim liquid directly or in an absorbent.<br>Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional advice | : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.<br>For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet. |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

---

### SECTION 7. HANDLING AND STORAGE

|                         |                                                                                                                                                                                                                                                                                                       |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Precautions     | : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.<br>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.         |
| Advice on safe handling | : Avoid prolonged or repeated contact with skin.<br>Avoid inhaling vapour and/or mists.<br>When handling product in drums, safety footwear should be worn and proper handling equipment should be used.<br>Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. |
| Avoidance of contact    | : Strong oxidising agents.                                                                                                                                                                                                                                                                            |
| Product Transfer        | : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.                                                                                                                                                                            |

#### Storage

|                    |                                                                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Other data         | : Keep container tightly closed and in a cool, well-ventilated place.<br>Use properly labeled and closable containers.<br><br>Store at ambient temperature. |
| Packaging material | : Suitable material: For containers or container linings, use mild steel or high density polyethylene.<br>Unsuitable material: PVC.                         |
| Container Advice   | : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.                                                |

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

| Components        | CAS-No.      | Value type<br>(Form of exposure)   | Control parameters / Permissible concentration | Basis    |
|-------------------|--------------|------------------------------------|------------------------------------------------|----------|
| Oil mist, mineral | Not Assigned | TWA (Mist)                         | 5 mg/m <sup>3</sup>                            | OSHA Z-1 |
|                   |              | TWA (Inhalable particulate matter) | 5 mg/m <sup>3</sup>                            | ACGIH    |

#### Biological occupational exposure limits

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

#### Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of



# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

### Personal protective equipment

Respiratory protection

: No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 09.06.2020          |
| 1.4     | 01.04.2020     | 800010016439 | Date of last issue: 18.12.2019  |
|         |                |              | Date of first issue: 16.02.2015 |

dependent on the exact composition of the glove material.  
Glove thickness should be typically greater than 0.35 mm  
depending on the glove make and model.

- |                          |                                                                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Eye protection           | : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.                                |
| Skin and body protection | : Skin protection is not ordinarily required beyond standard work clothes.<br>It is good practice to wear chemical resistant gloves. |
| Thermal hazards          | : Not applicable                                                                                                                     |
| Protective measures      | : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.                          |

### Environmental exposure controls

- |                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice | : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.<br>Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- |                                         |                                           |
|-----------------------------------------|-------------------------------------------|
| Appearance                              | : liquid                                  |
| Colour                                  | : Not applicable                          |
| Odour                                   | : Slight hydrocarbon                      |
| Odour Threshold                         | : Data not available                      |
| pH                                      | : Not applicable                          |
| pour point                              | : -45 °C / -49 °F<br>Method: ASTM D97     |
| Initial boiling point and boiling range | : > 280 °C / 536 °F<br>estimated value(s) |
| Flash point                             | : 188 °C / 370 °F                         |

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

---

Method: ASTM D92 (COC)

|                                        |                                                                                                                |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Evaporation rate                       | : Data not available                                                                                           |
| Flammability (solid, gas)              | : Data not available                                                                                           |
| Upper explosion limit                  | : Typical 10 %(V)                                                                                              |
| Lower explosion limit                  | : Typical 1 %(V)                                                                                               |
| Vapour pressure                        | : < 0.5 Pa (20 °C / 68 °F)<br>estimated value(s)                                                               |
| Relative vapour density                | : > 1<br>estimated value(s)                                                                                    |
| Relative density                       | : 0.865 (15 °C / 59 °F)                                                                                        |
| Density                                | : 865 kg/m3 (15.0 °C / 59.0 °F)Method: ASTM D4052                                                              |
| Solubility(ies)                        |                                                                                                                |
| Water solubility                       | : negligible                                                                                                   |
| Solubility in other solvents           | : Data not available                                                                                           |
| Partition coefficient: n-octanol/water | : log Pow: > 6<br>(based on information on similar products)                                                   |
| Auto-ignition temperature              | : > 320 °C / 608 °F                                                                                            |
| Decomposition temperature              | : Data not available                                                                                           |
| Viscosity                              |                                                                                                                |
| Viscosity, dynamic                     | : Data not available                                                                                           |
| Viscosity, kinematic                   | : 175 mm2/s (40.0 °C / 104.0 °F)<br>Method: ASTM D445<br><br>24.6 mm2/s (100 °C / 212 °F)<br>Method: ASTM D445 |
| Explosive properties                   | : Not classified                                                                                               |
| Oxidizing properties                   | : Data not available                                                                                           |
| Conductivity                           | : This material is not expected to be a static accumulator.                                                    |

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

addition to those listed in the following sub-paragraph.

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| Chemical stability                 | : Stable.                                             |
| Possibility of hazardous reactions | : Reacts with strong oxidising agents.                |
| Conditions to avoid                | : Extremes of temperature and direct sunlight.        |
| Incompatible materials             | : Strong oxidising agents.                            |
| Hazardous decomposition products   | : No decomposition if stored and applied as directed. |

### SECTION 11. TOXICOLOGICAL INFORMATION

|                      |                                                                                                                                                                                                                                     |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Basis for assessment | : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

|                           |                                                                                                                               |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity       | : LD50 (rat): > 5,000 mg/kg<br>Remarks: Low toxicity:<br>Based on available data, the classification criteria are not met.    |
| Acute inhalation toxicity | : Remarks: Based on available data, the classification criteria are not met.                                                  |
| Acute dermal toxicity     | : LD50 (Rabbit): > 5,000 mg/kg<br>Remarks: Low toxicity:<br>Based on available data, the classification criteria are not met. |

##### Components:

##### Polyolefin:

|                           |                                                                                                                                                                                                                                                            |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute inhalation toxicity | : Remarks: Mortality observed is due to aspiration of the material into the lungs, rather than intrinsic toxicity of the test substance. Acute toxicity caused by inhalation of this material is considered to be a highly unrealistic scenario in humans. |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Skin corrosion/irritation

##### Product:

Remarks: Slightly irritating to skin.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

#### Product:

Remarks: Slightly irritating to the eye.

Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

#### Product:

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

### Components:

#### **Alkyl amine:**

Remarks: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation.

May cause an allergic skin reaction in sensitive individuals.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo

: Remarks: Non mutagenic

Based on available data, the classification criteria are not met.

### Carcinogenicity

#### Product:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

#### **IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### **OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

#### Product:

Effects on fertility

:

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

---

Remarks: Not a developmental toxicant.  
Does not impair fertility.  
Based on available data, the classification criteria are not met.

### STOT - single exposure

**Product:**

Remarks: Based on available data, the classification criteria are not met.

### STOT - repeated exposure

**Product:**

Remarks: Based on available data, the classification criteria are not met.

### Aspiration toxicity

**Product:**

Not an aspiration hazard.

### Further information

**Product:**

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

---

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

### Ecotoxicity

**Product:**

Toxicity to fish (Acute toxicity)

Remarks: LL/EL/IL50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

Toxicity to crustacean (Acute toxicity) :  
Remarks: LL/EL/IL50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants (Acute toxicity) :  
Remarks: LL/EL/IL50 > 100 mg/l  
Practically non toxic:  
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

### **Components:**

#### **Alkenyl amine:**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10

### **Persistence and degradability**

#### **Product:**

Biodegradability : Remarks: Not readily biodegradable.  
Major constituents are inherently biodegradable, but contains components that may persist in the environment.

### **Bioaccumulative potential**

#### **Product:**

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: > 6  
Remarks: (based on information on similar products)

### **Mobility in soil**

#### **Product:**

Mobility : Remarks: Liquid under most environmental conditions.  
If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

Version  
1.4

Revision Date:  
01.04.2020

SDS Number:  
800010016439

Print Date: 09.06.2020  
Date of last issue: 18.12.2019  
Date of first issue: 16.02.2015

---

### Other adverse effects

#### Product:

Additional ecological information

: Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential. Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.  
Causes physical fouling of aquatic organisms.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues

: Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.

Contaminated packaging

: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation  
Remarks

: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

---

## SECTION 14. TRANSPORT INFORMATION

### National Regulations

#### TDG

Not regulated as a dangerous good

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good



# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 09.06.2020          |
| 1.4     | 01.04.2020     | 800010016439 | Date of last issue: 18.12.2019  |
|         |                |              | Date of first issue: 16.02.2015 |

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

### The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

DSL : All components listed.

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Pennzoil Platinum Axle 75W-140

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 09.06.2020          |
| 1.4     | 01.04.2020     | 800010016439 | Date of last issue: 18.12.2019  |
|         |                |              | Date of first issue: 16.02.2015 |

Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date : 01.04.2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN