



# Gas Line Antifreeze & Water Remover

### **SECTION 1. IDENTIFICATION**

**Product Identifier** Gas Line Antifreeze & Water Remover

**Other Means of** 35-311C, 35-315C

Identification

**Recommended Use** Please refer to Product label.

Restrictions on Use None known.

Manufacturer / Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory

**Supplier** Department, 905-878-5544, www.recochem.com

Emergency Phone No. CANUTEC, 613-996-6666, 24 Hours

**SDS No.** 1616

# **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Flammable liquid - Category 2; Serious eye damage/eye irritation - Category 2A

#### **GHS Label Elements**





Signal Word: Danger

#### Hazard Statement(s):

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

### Precautionary Statement(s):

### Prevention:

P210 Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting, and other equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P264 Wash hands and skin thoroughly after handling.

P280 Wear eye protection/face protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616 Page 01 of 08

and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use appropriate foam, carbon dioxide, dry chemical powder, water spray or fog to extinguish.

Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

#### Other Hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance:

Chemical Name	CAS No.	%	Other Identifiers
Ethanol	64-17-5	60-100	

### **SECTION 4. FIRST-AID MEASURES**

#### **First-aid Measures**

#### Inhalation

Take precautions to prevent a fire (e.g. remove sources of ignition). Remove source of exposure or move to fresh air. Get medical advice/attention if you feel unwell or are concerned.

#### Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. Get medical advice/attention if you feel unwell or are concerned. If skin irritation occurs get medical advice/attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

# **Eye Contact**

Avoid direct contact. Wear chemical protective gloves if necessary. Quickly and gently blot or brush chemical off the face. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists, get medical advice/attention.

### Ingestion

Rinse mouth with water. Get medical advice/attention if you feel unwell or are concerned.

# Most Important Symptoms and Effects, Acute and Delayed

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

### **Immediate Medical Attention and Special Treatment**

# **Target Organs**

Skin.

#### **Special Instructions**

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

#### **Medical Conditions Aggravated by Exposure**

None known.

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616 Page 02 of 08

# **SECTION 5. FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

### **Suitable Extinguishing Media**

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

### **Unsuitable Extinguishing Media**

None known.

### **Specific Hazards Arising from the Chemical**

Highly flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. Can be ignited by static discharge. Can accumulate static charge by flow, splashing or agitation. See Section 9 (Physical and Chemical Properties) for flash point and explosive limits. Closed containers may rupture violently when heated releasing contents.

In a fire, the following hazardous materials may be generated: very toxic carbon monoxide, carbon dioxide.

# **Special Protective Equipment and Precautions for Fire-fighters**

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills. See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

# Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Evacuate downwind locations. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Increase ventilation to area or move leaking container to a well-ventilated and secure area. Eliminate all ignition sources. Use grounded, explosion-proof equipment. Distant ignition and flashback are possible.

#### **Environmental Precautions**

Do not allow into any sewer, on the ground or into any waterway.

### Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

### **SECTION 7. HANDLING AND STORAGE**

### **Precautions for Safe Handling**

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Conditions for Safe Storage**

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616

Date of Preparation: November 18, 2015

Page 03 of 08

sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

	ACGIH TLV®		OSHA PEL		AIHA WEEL	
Chemical Name	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Ethanol	1000 ppm	1000 ppm	1000 ppm			

### **Appropriate Engineering Controls**

General ventilation is usually adequate. For large scale use of this product: do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Use only non-combustible, compatible materials for walls, floors, ventilation system, air cleaning devices, pallets, shelving. Provide eyewash and safety shower if contact or splash hazard exists.

### **Individual Protection Measures**

### **Eye/Face Protection**

Wear chemical safety goggles.

#### **Skin Protection**

Wear chemical protective clothing e.g. gloves, aprons, boots.

### **Respiratory Protection**

Not normally required if product is used as directed.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

# **Basic Physical and Chemical Properties**

AppearanceClear liquid.OdourNot availableOdour ThresholdNot available

**pH** 7

Melting Point/Freezing Point -114 °C (-173 °F) (melting); -114 °C (-173 °F) (freezing)

Initial Boiling Point/Range 78 °C (172 °F)

Flash Point 13 °C (55 °F) (closed cup) Evaporation Rate 2.4 (n-butyl acetate = 1)

Flammability (solid, gas) Not applicable

Upper/Lower Flammability or

**Explosive Limit** 

15% (upper); 3.3% (lower)

Vapour Pressure 44.3 mm Hg (5.9 kPa) at 20 °C

Vapour Density (air = 1) 1.59

Relative Density (water = 1) 0.79 - 0.81 at 20 °C

**Soluble** in water; Soluble in all proportions in common organic solvents.

Partition Coefficient, Not available

n-Octanol/Water (Log Kow)

**Auto-ignition Temperature** 363 °C (685 °F) **Decomposition Temperature** Not available

Viscosity 1.47 mm2/s at 20 °C (kinematic); 1.17 mPa.s at 20 °C (dynamic)

Other Information

Physical State Liquid

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616 Page 04 of 08

# **SECTION 10. STABILITY AND REACTIVITY**

### Reactivity

None known.

#### **Chemical Stability**

Normally stable.

#### **Possibility of Hazardous Reactions**

None known.

#### **Conditions to Avoid**

Open flames, sparks, static discharge, heat and other ignition sources. Temperatures above 12.0 °C (53.6 °F)

# **Incompatible Materials**

Strong oxidizing agents (e.g. perchloric acid), strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide).

#### **Hazardous Decomposition Products**

Very toxic carbon monoxide, carbon dioxide; toxic chemicals.

# **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Likely Routes of Exposure**

Ingestion; skin contact.

### **Acute Toxicity**

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Ethanol	21000 mg/m3 (mouse) (4-hour exposure)	3450 mg/kg (mouse)	> 15800 mg/kg (rabbit)

LC50: Not applicable.

LD50 (oral): Not applicable. LD50 (dermal): Not applicable.

#### Skin Corrosion/Irritation

Human experience and animal tests show no or very mild irritation.

# Serious Eye Damage/Irritation

Human experience and animal tests show serious eye irritation.

# STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

May be harmful as a mist nose and throat irritation.

May be harmful as a mist at high concentrations depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. A severe exposure can cause unconsciousness.

### **Skin Absorption**

Not harmful based on human experience and animal tests.

#### Ingestion

May be harmful based on human experience. Depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. A severe exposure can cause unconsciousness.

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616 Page 05 of 08

### **Aspiration Hazard**

Not known to be an aspiration hazard.

### STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause Following skin contact: dermatitis.

### Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer.

Human experience shows an allergic skin reaction (skin sensitization) in rare cases following exposure at work.

### Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Ethanol	Group 1	A3	Not Listed	Not Listed

Carcinogenicity classification is based on alcoholic beverage consumption and not relevant to occupational exposures.

Key to Abbreviations

A3 = Animal carcinogen.

### **Reproductive Toxicity**

### **Development of Offspring**

May harm the unborn child. However, these effects are only seen with significant toxicity in the mothers. Known to cause: embryotoxic (late resorptions) teratogenic(external, soft tissue and skeletal defects) decreased weight. These effects are not considered relevant to occupational exposures.

### **Sexual Function and Fertility**

Studies in people and animals show effects on sexual function and/or fertility. Known to cause: effects in men and women. These effects are not considered relevant to occupational exposures.

#### Effects on or via Lactation

Can transfer to mother's milk.

### **Germ Cell Mutagenicity**

Causes mutagenicity in non-reproductive (somatic) cells in tests using live animals. These effectrs are not considered relevant to occupational exposures.

#### Interactive Effects

No information was located.

### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Toxicity**

### **Acute Aquatic Toxicity**

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
	42 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)	2 mg/L (Daphnia magna (water flea); 48-hour; fresh water)		

### **Chronic Aquatic Toxicity**

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Ethanol			< 6300 mg/L (Daphnia magna (water flea); fresh water)	

# Persistence and Degradability

No information was located.

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616

Date of Preparation: November 18, 2015

Page 06 of 08

#### **Bioaccumulative Potential**

No information was located.

#### **Mobility in Soil**

No information was located.

#### Other Adverse Effects

There is no information available.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14. TRANSPORT INFORMATION**

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1987	ALCOHOLS, N.O.S. (Ethanol)	3	II
US DOT	1987	ALCOHOLS, N.O.S. (Ethanol)	3	II

Environmental Hazards Not applicable

**Special Precautions** 

for User

Please note: In containers of 1 L (1Kg) capacity or less this product is classified as a "Limited

Quantities""Consumer Commodity" under TDG regulations.

In containers of 1 L (1Kg) this product is qualified as a "consumer commodity" ORM-D under

DOT

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15. REGULATORY INFORMATION**

### Safety, Health and Environmental Regulations

#### Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

#### **USA**

### **Toxic Substances Control Act (TSCA) Section 8(b)**

All ingredients are listed on the TSCA Inventory.

# **SECTION 16. OTHER INFORMATION**

SDS Prepared By Compliance and Regulatory Department

Phone No. 905-878-5544 **Date of Preparation** November 18, 2015

Additional Information We are committed to uphold the Industry Consumer Ingredient Communication Voluntary

Initiative

Please send us your request by visiting our website at www.recochem.com.

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616 Page 07 of 08

**Disclaimer** 

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: Gas Line Antifreeze & Water Remover

SDS No.: 1616

