

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

1 Identification

- **Product identifier**
- **Trade name:** Hy-Per Lube Total Fuel System Cleaner
- **Product code:** HPF200C
- **Recommended use and restriction on use**
- **Recommended use:** Additive
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Hy-per Lube
P.O. Box 187
Holly, MI 48442 USA
Phone: (810) 603-1321
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)



2 Hazard(s) identification

- **Classification of the substance or mixture**
 Flam. Liq. 3 H226 Flammable liquid and vapor.
 Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Carc. 2 H351 Suspected of causing cancer.
 STOT SE 1 H370 Causes damage to organs.
 STOT RE 2 H373 May cause damage to the liver, the bone marrow, the thymus and the gastro-intestinal tract through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS07 GHS08

- **Signal word:** Danger

- **Hazard statements:**

H226 Flammable liquid and vapor.
 H332 Harmful if inhaled.
 H315 Causes skin irritation.
 H351 Suspected of causing cancer.
 H370 Causes damage to organs.
 H373 May cause damage to the liver, the bone marrow, the thymus and the gastro-intestinal tract through prolonged or repeated exposure.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 1)

H304 May be fatal if swallowed and enters airways.

Precautionary statements:










- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Components:

68476-34-6	Fuels, diesel, No 2  Flam. Liq. 3, H226  Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332; Skin Irrit. 2, H315	30-50%
8008-20-6	Kerosine (petroleum)  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	20-40%
1159170-26-9	Fuels, diesel, C9-18-alkane branched and linear  Flam. Liq. 3, H226  Carc. 2, H351; STOT SE 1, H370; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335-H336	<10%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	<10%

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 2)

	Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Flam. Liq. 4, H227	
928771-01-1	alkanes, C10-20-branched and linear Asp. Tox. 1, H304	<10%
64771-72-8	Paraffins (petroleum), normal C5-20 Asp. Tox. 1, H304 Flam. Liq. 4, H227	<10%
1330-20-7	Xylene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<10%
91-20-3	Naphthalene Flam. Sol. 2, H228 Carc. 2, H351 Acute Tox. 4, H302	<1%
100-41-4	Ethylbenzene Flam. Liq. 2, H225 Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332	<1%
95-63-6	1,2,4-trimethylbenzene Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<1%

· **Additional information:** For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.
 Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately remove any clothing soiled by the product.
 Immediately wash with water and soap and rinse thoroughly.
 Seek medical treatment in case of complaints.

· After eye contact:

Remove contact lenses if worn.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; immediately call for medical help.
 A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed:

Coughing
 Dizziness
 Breathing difficulty

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 3)

Gastric or intestinal disorders

Irritant to skin and mucous membranes.

· **Danger:**

Danger of impaired breathing.

May be fatal if swallowed and enters airways.

Harmful if inhaled.

May cause cancer.

· **Indication of any immediate medical attention and special treatment needed:**

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Monitor circulation, possible shock treatment.

Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Foam

Alcohol resistant foam

Gaseous extinguishing agents

Carbon dioxide

Fire-extinguishing powder

Water fog / haze

· **For safety reasons unsuitable extinguishing agents:**

Water stream.

Water spray

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information:** Cool endangered containers with water fog.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Particular danger of slipping on leaked/spilled product.

· **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up**

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 4)

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Remove from the water surface (e.g. skim or suck off).
Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Keep out of reach of children.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Keep respiratory protective device available.
Keep ignition sources away - Do not smoke.

· **Conditions for safe storage, including any incompatibilities**

· **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.
Store in cool, dry conditions in well sealed receptacles.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.
Store away from oxidizing agents.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

68476-34-6 Fuels, diesel, No 2

TLV (USA)	Long-term value: 100* mg/m ³ as total hydrocarbons; Skin; *inh. fraction + vapor
EL (Canada)	Long-term value: 100 mg/m ³ vapour and inhalable aerosol; Skin, IARC 2B
EV (Canada)	Long-term value: 100 mg/m ³ as total hydrocarbons, vapour and aerosol, Skin
LMPE (Mexico)	Long-term value: 100 mg/m ³ A3, PIEL, IFV

8008-20-6 Kerosine (petroleum)

REL (USA)	Long-term value: 100 mg/m ³ Kerosine only
TLV (USA)	Long-term value: 200 mg/m ³ as total hydrocarbon vapor; Skin; P

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 5)

EL (Canada)	Long-term value: 200 mg/m ³ Skin
EV (Canada)	Long-term value: 200(G) mg/m ³ as total hydrocarbon vapour, Skin
LMPE (Mexico)	Long-term value: 200 mg/m ³ A3, PIEL

1330-20-7 Xylene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

91-20-3 Naphthalene

PEL (USA)	Long-term value: 50 mg/m ³ , 10 ppm
REL (USA)	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm
TLV (USA)	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI
EL (Canada)	Long-term value: 10 ppm Skin; IARC 2B
EV (Canada)	Short-term value: 78 mg/m ³ , 15 ppm Long-term value: 52 mg/m ³ , 10 ppm
LMPE (Mexico)	Short-term value: 15 ppm Long-term value: 10 ppm A4, PIEL

100-41-4 Ethylbenzene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 87 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

95-63-6 1,2,4-trimethylbenzene

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 6)

REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm

Ingredients with biological limit values:

1330-20-7 Xylene

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

100-41-4 Ethylbenzene

BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

Exposure controls

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

Engineering controls: No relevant information available.

Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:



Safety glasses

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

No relevant information available.

Risk management measures No relevant information available.

9 Physical and chemical properties

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 7)

Information on basic physical and chemical properties

Appearance:

Form: Liquid

Color: Red

Odor: Petroleum-like

Odor threshold: Not determined.

pH-value: Not determined.

Melting point/Melting range: Not determined.

Boiling point/Boiling range: Not determined.

Flash point: 57.2 °C (135 °F)

Flammability (solid, gaseous): Not applicable.

Auto-ignition temperature: Not determined.

Decomposition temperature: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Explosion limits

Lower: Not determined.

Upper: Not determined.

Oxidizing properties: Non-oxidizing.

Vapor pressure: Not determined.

Density:

Relative density: 0.813-0.848

Vapor density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity

Dynamic: Not determined.

Kinematic: Not determined.

Other information: No relevant information available.

10 Stability and reactivity

Reactivity: No relevant information available.

Chemical stability:

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Flammable liquid and vapor.

Used empty containers may contain product gases which form explosive mixtures with air.

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 8)

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Reacts with oxidizing agents.

- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Under fire conditions only:
Carbon monoxide and carbon dioxide

11 Toxicological information

· Information on toxicological effects

- **Acute toxicity:** Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

68476-34-6 Fuels, diesel, No 2

Inhalative	LC50/4h	5.4 mg/l (rat)
------------	---------	----------------

91-20-3 Naphthalene

Oral	LD50	490 mg/kg (rat)
------	------	-----------------

Dermal	LD50	5000 mg/kg (rat)
--------	------	------------------

· Primary irritant effect:

- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** No sensitizing effects known.

· IARC (International Agency for Research on Cancer):

68476-34-6	Fuels, diesel, No 2	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B

· NTP (National Toxicology Program):

91-20-3	Naphthalene	R
---------	-------------	---

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

- **Carcinogenicity:** Suspected of causing cancer.

- **Reproductive toxicity:** Based on available data, the classification criteria are not met.

- **STOT-single exposure:** Causes damage to organs.

- **STOT-repeated exposure:**

May cause damage to the liver, the bone marrow, the thymus and the gastro-intestinal tract through prolonged or repeated exposure.

- **Aspiration hazard:** May be fatal if swallowed and enters airways.

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 9)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity**
Toxic to aquatic life with long lasting effects.

91-20-3 Naphthalene

LC50 1-10 mg/l (daphnia)

- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information**
- **General notes:** Avoid transfer into the environment.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Contact waste processors for recycling information.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT** NA1993
- **ADR/RID/ADN, IMDG, IATA** UN1268
- **UN proper shipping name**
- **DOT** Combustible liquid, n.o.s. (Diesel Fuel, Naphtha)
- **ADR/RID/ADN, IMDG** PETROLEUM PRODUCTS, N.O.S. (Diesel Fuel, Naphtha)
- **IATA** Petroleum products, n.o.s. (Diesel Fuel, Naphtha)
- **Transport hazard class(es)**
- **DOT**



(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 10)

· Class 3
· Label 3

· ADR/RID/ADN



· Class 3 (F1)
· Label 3

· IMDG, IATA



· Class 3
· Label 3

· Packing group III
· DOT, ADR/RID/ADN, IMDG, IATA

· Environmental hazards Product contains environmentally hazardous substances: Fuels, diesel, No 2, Naphthalene

· Marine pollutant:



Yes

· Special precautions for user Warning: Flammable liquids
· Danger code (Kemler): 30
· EMS Number: F-E, S-E

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥ 119 US gal / 450 L. Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· ADR/RID/ADN



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

(Cont'd. on page 12)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 11)

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· IMDG



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

68476-34-6 Fuels, diesel, No 2

91-20-3 Naphthalene

100-41-4 Ethylbenzene

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

(Cont'd. on page 13)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 12)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

1330-20-7	Xylene	I
91-20-3	Naphthalene	C, CBD

· **IARC (International Agency for Research on Cancer):**

68476-34-6	Fuels, diesel, No 2	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Flam. Sol. 2: Flammable solids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

(Cont'd. on page 14)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 19, 2019

Trade name: Hy-Per Lube Total Fuel System Cleaner

(Cont'd. of page 13)

Website: www.chemtelinc.com