

ZIEX ZE960 A/S



Rim Diameter	Item Number	Tire Size	Load ID	Service Desc.	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load (lbs)	Max Pressure (psi cold)	U.T.Q.G.
15"	28962571	195/50R15	SL	82V	5.5 - 7.0	6.0	22.7	7.9	921	10	17.6	1047	51	640-A-A
	28961543	195/65R15	SL	91H	5.5 - 7.0	6.0	25.1	8.0	845	10	19.8	1356	51	640-A-A
	28962544	205/65R15	XL	99V	5.5 - 7.5	6.0	25.6	8.3	832	10	21.8	1709	50	640-A-A
16"	28962660	195/50R16	SL	84V	5.5 - 7.0	6.0	23.7	7.9	883	10	19.4	1102	51	640-A-A
	28962615	195/55R16	SL	87V	5.5 - 7.0	6.0	24.4	7.9	862	10	20.3	1201	51	640-A-A
	28962690	205/45R16	XL	87V	6.5 - 7.5	7.0	23.3	8.1	895	10	19.2	1201	50	640-A-A
	28962671	205/50R16	SL	87V	5.5 - 7.5	6.5	24.1	8.4	874	10	20.5	1201	51	640-A-A
	28962483	205/55R16	SL	91V	5.5 - 7.5	6.5	24.9	8.4	845	10	21.4	1356	51	640-A-A
	28962652	205/60R16	SL	92V	5.5 - 7.5	6.0	25.8	8.3	821	10	21.8	1389	51	640-A-A
	28962626	205/65R16	SL	95V	5.5 - 7.5	6.0	26.5	8.3	800	10	22.0	1521	51	640-A-A
	28962662	215/55R16	XL	97V	6.0 - 7.5	7.0	25.3	8.9	834	10	23.6	1609	50	640-A-A
	28962479	215/60R16	SL	95V	6.0 - 7.5	6.5	26.3	8.8	811	10	22.9	1521	51	640-A-A
	28962670	225/55R16	SL	95V	6.0 - 8.0	7.0	25.7	9.2	821	10	24.0	1521	51	640-A-A
	28962480	225/60R16	SL	98V	6.0 - 8.0	6.5	26.7	9.1	795	10	25.1	1653	51	640-A-A
	28963674	245/50R16	SL	97W	7.0 - 8.5	7.5	25.7	10.0	821	10	25.1	1609	51	540-A-A
17"	28963740	205/40R17	XL	84W	7.0 - 8.0	7.5	23.5	8.3	886	10	20.3	1102	50	540-A-A
	28963781	205/45R17	XL	88W	6.5 - 7.5	7.0	24.3	8.1	856	10	20.9	1235	50	540-A-A
	28962770	205/50R17	XL	93V	5.5 - 7.5	6.5	25.1	8.4	837	10	21.4	1433	50	640-A-A
	28962792	215/45R17	XL	91V	7.0 - 8.0	7.0	24.7	8.4	842	10	22.0	1356	50	640-A-A
	28962771	215/50R17	SL	91V	6.0 - 7.5	7.0	25.5	8.9	823	10	21.8	1356	51	640-A-A
	28962727	215/55R17	SL	94V	6.0 - 7.5	7.0	26.3	8.9	800	10	22.7	1477	51	640-A-A
	28962782	215/65R17	SL	99V	6.0 - 7.5	6.5	28.1	8.8	755	10	26.7	1709	51	640-A-A

ZIEX ZE960 A/S



Rim Diameter	Item Number	Tire Size	Load ID	Service Desc.	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load (lbs)	Max Pressure (psi cold)	U.T.Q.G.
18"	28963795	225/45R17	XL	94W	7.0 - 8.5	7.5	25	8.9	834	10	24.0	1477	50	540-A-A
	28962772	225/50R17	SL	94V	6.0 - 8.0	7.0	25.9	9.2	811	10	23.6	1477	51	640-A-A
	28962762	225/55R17	XL	101V	6.0 - 8.0	7.0	26.8	9.2	788	10	26.5	1819	50	640-A-A
	28962794	235/45R17	XL	97V	7.5 - 9.0	8.0	25.4	9.3	821	10	25.4	1609	50	640-A-A
	28962773	235/50R17	SL	96V	6.5 - 8.5	7.5	26.3	9.6	800	10	24.9	1565	51	640-A-A
	28963725	235/55R17	SL	99W	6.5 - 8.5	7.5	27.2	9.6	778	10	27.6	1709	51	540-A-A
	28963785	245/40R17	XL	95W	8.0 - 9.5	8.5	24.7	9.8	840	10	26.7	1521	50	540-A-A
	28963784	245/45R17	XL	99W	7.5 - 9.0	8.0	25.7	9.6	813	10	26.0	1709	50	540-A-A
	28963776	245/50R17	SL	99W	7.0 - 8.5	7.5	26.7	10.0	788	10	27.8	1709	51	540-A-A
	28963891	215/40R18	XL	89W	7.0 - 8.5	7.5	24.8	8.6	837	10	22.7	1279	50	540-A-A
	28963899	215/45R18	XL	93W	7.0 - 8.0	7.0	25.7	8.4	808	10	23.4	1433	50	540-A-A
	28963892	225/40R18	XL	92W	7.5 - 9.0	8.0	25.1	9.1	826	10	23.8	1389	50	540-A-A
	28963824	225/45R18	XL	95W	7.0 - 8.5	7.5	26	8.9	800	10	24.9	1521	50	540-A-A
	28963805	225/50R18	SL	95W	6.0 - 8.0	7.0	26.9	9.2	778	10	24.7	1521	51	540-A-A
	28963893	235/40R18	XL	95W	8.0 - 9.5	8.5	25.4	9.5	818	10	26.2	1521	50	540-A-A
	28963895	235/45R18	SL	94W	7.5 - 9.0	8.0	26.4	9.3	788	10	26.5	1477	51	540-A-A
	28963825	235/50R18	XL	101W	6.5 - 8.5	7.5	27.3	9.6	769	10	26.7	1819	50	540-A-A
	28962817	235/55R18	XL	104V	6.5 - 8.5	7.5	28.1	9.6	749	10	30.2	1984	50	640-A-A
	28963894	245/40R18	XL	97W	8.0 - 9.5	8.5	25.7	9.8	805	10	27.6	1609	50	540-A-A
	28962865	245/45R18	XL	100V	7.5 - 9.0	8.0	26.7	9.6	781	10	27.8	1764	50	640-A-A
	28963863	245/55R18	SL	103W	7.0 - 8.5	7.5	28.6	10.0	736	10	30.2	1929	51	540-A-A
	28963844	255/40R18	XL	99W	8.5 - 10.0	9.0	26	10.2	798	10	28.4	1709	50	540-A-A

ZIEX ZE960 A/S



Rim Diameter	Item Number	Tire Size	Load ID	Service Desc.	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load (lbs)	Max Pressure (psi cold)	U.T.Q.G.
19"	28963866	255/45R18	XL	103W	8.0 - 9.5	8.5	27.1	10.0	771	10	27.3	1929	50	540-A-A
	28963937	225/45R19	XL	96W	7.0 - 8.5	7.5	27	8.9	769	10	25.6	1565	50	540-A-A
	28962495	235/40R19	XL	96V	8.0 - 9.5	8.5	26.4	9.5	786	10	26.2	1565	50	640-A-A
	28963974	245/40R19	SL	94W	8.0 - 9.5	8.5	26.7	9.8	774	10	28.0	1477	51	540-A-A
20"	28962997	255/45R19	SL	100V	8.0 - 9.5	8.5	28.1	10.0	742	10	29.5	1764	51	640-A-A
	28963985	245/35R20	XL	95W	8.0 - 9.5	8.5	26.8	9.8	774	10	28.0	1521	50	540-A-A
	28963002	245/40R20	XL	99W	8.0 - 9.5	8.5	27.7	9.8	747	10	29.8	1709	50	540-A-A
	28963023	245/45R20	XL	103W	7.5 - 9.0	8.0	28.7	9.6	725	10	29.8	1929	50	540-A-A
	28963001	255/35R20	XL	97W	8.5 - 10.0	9.0	27	10.2	767	10	28.0	1609	50	540-A-A