

ZIEX CT60 A/S



Rim Diameter	Item Number	Tire Size	Load ID	Service Desc.	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load (lbs)	Max Pressure (psi cold)	U.T.Q.G.
16"	28041481	205/70R16	SL	97H	5.0 - 7.0	6	27.3	8.2	770	10	25.1	1609	51	740-A-A
	28042275	215/65R16	XL	102V	6.0 - 7.5	6.5	27.0	8.62	786	10.16	25.6	1874	50	680-A-A
	28043229	215/70R16	SL	100H	5.5 - 7.0	6.5	27.9	8.62	756	10.28	26.1	1764	51	740-A-A
	28047319	225/70R16	SL	103H	6.0 - 7.5	6.5	28.4	8.9	741	10.4	28	1929	51	740-A-A
	28045157	235/70R16	SL	106H	6.0 - 8.0	7	29.0	9.37	729	10.52	28.7	2094	51	740-A-A
17"	28047536	215/60R17	XL	100V	6.0 - 7.5	6.5	27.2	8.62	777	10.04	25.6	1764	50	680-A-A
	28049959	225/60R17	SL	99V	6.0 - 8.0	6.5	27.6	8.9	764	10.16	27.8	1709	51	740-A-A
	28046926	225/65R17	SL	102H	6.0 - 8.0	6.5	28.6	8.86	741	10.28	28	1874	51	740-A-A
	28042725	235/55R17	SL	99V	6.5 - 8.5	7.5	27.0	9.8	744	11	28.9	1709	51	740-A-A
	28048361	235/60R17	SL	102H	6.5 - 8.5	7	28.1	9.37	753	10.28	30	1874	51	740-A-A
18"	28044862	235/65R17	SL	104V	6.5 - 8.5	7	29.1	9.37	731	10.4	30.4	1984	51	740-A-A
	28042900	215/55R18	SL	95V	6.0 - 7.5	7	27.2	9	742	10	25.6	1521	51	740-A-A
	28047926	225/55R18	SL	98V	6.0 - 8.0	7	27.8	9.09	758	10.16	27.1	1653	51	740-A-A
	28041826	225/60R18	SL	100H	6.0 - 8.0	6.5	28.6	9	738	10	28.7	1764	51	740-A-A
	28042903	235/50R18	SL	97V	6.5 - 8.5	7.5	27.3	9.57	771	10.28	28.4	1609	51	740-A-A
	28046809	235/55R18	SL	100V	6.5 - 8.5	7.5	28.2	9.57	748	10.28	28.9	1764	51	740-A-A
	28043236	235/60R18	XL	107V	6.5 - 8.5	7	29.1	9.37	726	10.28	30.9	2149	50	680-A-A
	28044742	235/65R18	SL	106V	6.5 - 8.5	7	30.0	9.37	705	10.4	32.4	2094	51	740-A-A
	28042820	245/50R18	SL	100V	7.0 - 8.5	7.5	27.7	10	728	11	30.6	1764	51	740-A-A
	28041117	245/60R18	SL	105V	7.0 - 8.5	7	29.6	9.69	716	10.4	35.1	2039	51	740-A-A
	28046594	255/55R18	XL	109V	7.0 - 9.0	8	29.0	10.35	728	10.52	33.7	2271	50	680-A-A
	28041812	255/60R18	SL	108H	7.0 - 9.0	7.5	30.0	10.2	705	11	34.2	2205	51	740-A-A

ZIEX CT60 A/S



Rim Diameter	Item Number	Tire Size	Load ID	Service Desc.	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load (lbs)	Max Pressure (psi cold)	U.T.Q.G.
19"	28041376	255/65R18	SL	111H	7.0 - 9.0	7.5	31.1	10.16	683	10.64	36.8	2403	51	740-A-A
	28042854	265/60R18	SL	110V	7.5 - 9.5	8	31.0	11	694	10	41	2337	51	600-A-A
	28041823	265/65R18	SL	114H	7.5 - 9.5	8	32.0	11	673	10	41.2	2601	51	600-A-A
	28041897	275/60R18	XL	117H	7.5 - 9.5	8	31.0	11	686	10	43	2833	50	600-A-A
	28042856	285/60R18	SL	116V	8.0 - 10.0	8.5	32.0	12	675	11	48.1	2756	51	600-A-A
	28043062	225/55R19	SL	99V	6.0 - 8.0	7	28.8	9.09	730	10.16	28.4	1709	51	740-A-A
	28046456	235/45R19	XL	99V	7.5 - 9.0	8	27.4	9.21	760	10.28	27	1709	50	680-A-A
	28045081	235/50R19	SL	99V	6.5 - 8.5	7.5	28.3	9.57	742	10.28	30.2	1709	51	740-A-A
	28042970	235/55R19	XL	105V	6.5 - 8.5	7.5	29.2	9.6	720	10	30.6	2039	50	680-A-A
	28042904	245/45R19	XL	102V	7.5 - 9.0	8	27.6	9.6	730	11	28.9	1874	50	680-A-A
	28047020	245/55R19	SL	103V	7.0 - 8.5	7.5	29.7	9.88	711	10.4	31.5	1929	51	740-A-A
	28042996	255/40R19	XL	100V	8.5 - 10.0	9	27.1	10.2	794	11	28.2	1764	50	680-A-A
	28045479	255/50R19	XL	107V	7.0 - 9.0	8	29.1	10.35	723	10.52	34.2	2149	50	680-A-A
	28042943	255/55R19	XL	111V	7.0 - 9.0	8	30.0	10.6	672	11	34.4	2403	50	680-A-A
	28045772	255/60R19	SL	109H	7.0 - 9.0	7.5	31.1	10.16	680	10.52	34.2	2271	51	740-A-A
20"	28047541	265/50R19	XL	110V	7.5 - 9.5	8.5	29.5	10.83	713	10.64	34.6	2337	50	680-A-A
	28042032	275/55R19	SL	111V	7.5 - 9.5	8.5	30.9	11.2	684	10	42.5	2403	51	600-A-A
	28048062	235/55R20	SL	102V	6.5 - 8.5	7.5	30.2	9.57	697	10.28	34.6	1874	51	740-A-A
	28048659	245/50R20	SL	102V	7.0 - 8.5	7.5	29.7	9.88	708	10.4	34.4	1874	51	740-A-A
	28042013	255/45R20	XL	105V	8.0 - 9.5	8.5	29.1	10	735	11	32.6	2039	50	680-A-A
	28043623	255/50R20	XL	109V	7.0 - 9.0	8	30.1	10.35	699	10.52	37.7	2271	50	680-A-A
	28042950	255/55R20	XL	110V	7.0 - 9.0	8	31.0	10.4	680	11	35.5	2337	50	680-A-A

ZIEX CT60 A/S



Rim Diameter	Item Number	Tire Size	Load ID	Service Desc.	Approved Rim Width (in)	Measuring Rim (in)	Overall Diameter (in)	Overall Width (in)	Revs Per Mile	Tread Depth (/32in)	Tire Weight (lbs)	Max Load (lbs)	Max Pressure (psi cold)	U.T.Q.G.
	28045726	265/50R20	XL	111V	7.5 - 9.5	8.5	30.5	10.83	690	10.64	36.8	2403	50	680-A-A
	28041828	245/60R20	SL	107H	7.0 - 8.5	7	32.0	10	668	10	39.9	2149	51	600-A-A
	28042587	265/45R20	XL	108V	8.5 - 10.0	9	29.0	11	709	10	36.4	2205	50	600-A-A
	28042016	275/45R20	XL	110V	8.5 - 10.5	9	30.0	11	700	10	38.1	2337	50	600-A-A
	28041777	275/50R20	SL	109H	7.5 - 9.5	8.5	31.0	11	681	10	41.7	2271	51	600-A-A
	28041021	275/55R20	XL	117H	7.5 - 9.5	8.5	32.0	11	661	10	46.3	2833	50	600-A-A
	28041003	275/60R20	XL	116H	7.5 - 9.5	8	33.0	11	641	10	46.3	2756	50	600-A-A
	28042024	285/50R20	SL	112V	8.0 - 10.0	9	31.0	12	673	11	44.3	2469	51	600-A-A
22"	28042035	275/50R22	SL	111V	7.5 - 9.5	8.5	33.0	11	638	10	49.6	2403	51	600-A-A
	28041219	285/45R22	XL	114H	9.0 - 10.5	9.5	32.0	11	647	11	47	2601	50	600-A-A