

GRABBER™ ARCTIC

WINTER STUDDABLE, DIRECTIONAL

WINTER WEATHER IS NO MATCH FOR THE GRABBER™ ARCTIC. A STUDDABLE, WINTER TIRE, THIS TIRE GIVES YOU OUTSTANDING LOW TEMPERATURE TRACTION IN SNOW, ICE AND WET CONDITIONS AND IS DURABLE, ROBUST AND COMFORTABLE FOR LARGE SUVS AND PICK-UP TRUCKS

DURAGEN™ Technology: A robust cut and chip resistant compound, combined with ultra high-strength steel belts and a broad contour, promote confident stability, even wear, excellent braking and responsive handling.

Directional Tread Pattern with Center Stability Rib: Provides active water evacuation and snow traction while the center rib provides straight-line stability.

Strong Interlocking Light Truck Winter Sipes Combined with Smooth Car-like Serrated Sipes: Exceptional grip in snow, ice and wet conditions while providing stable handling and strong braking in dry and wet conditions. Combination of truck and car sipes provide durability and comfort.

Pinned for Winter Studs: For those that desire the added ice grip winter studs provide.

Tread Block Reinforcement Buttresses: Add strength and stability to tread blocks, providing improved handling and improved wet and dry braking performance.



45
DAY TRIAL
OR THE FIRST 2/32" OF TREAD

See warranty manual for complete details.



Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).

GENERAL TIRE 

Size	Load/Speed	Load Range	Sidewall	Article Number	Rim Protect	Tire Diameter (in)	Tire Weight (lbs)	MAX. PSI	Approved Rim Width (in)	MAX. Load (lbs)	Tread Depth (in - 32nds)	Revs Per Mile
235/70 R 16	109 T	XL	BSW	15503280000	Yes	29.0	31.1	51	(6.0 - 8.0)	2,271	12	718
245/75 R 16	115 T	XL	BSW	15503330000	Yes	30.5	32.6	51	(6.5 - 8.0)	2,679	12	682
265/70 R 16	116 T	XL	BSW	15503340000	Yes	30.6	37.7	51	(7.0 - 9.0)	2,756	12	679
245/65 R 17	111 T	XL	BSW	15503260000	Yes	29.5	33.3	51	(7.0 - 8.5)	2,403	12	703
245/70 R 17	114 T	XL	BSW	15503290000	Yes	30.5	33.4	51	(6.5 - 8.0)	2,601	12	681
265/65 R 17	116 T	XL	BSW	15503370000	Yes	30.6	35.1	51	(7.5 - 9.5)	2,756	12	680
265/70 R 17	116 T	XL	BSW	15502540000	Yes	31.6	37.3	51	(7.0 - 9.0)	2,756	12	657
245/60 R 18	109 T	XL	BSW	15503310000	Yes	29.6	33.1	51	(7.0 - 8.5)	2,271	12	702
255/55 R 18	109 T	XL	BSW	15502560000	Yes	29.0	32.3	51	(7.0 - 9.0)	2,271	12	715
255/65 R 18	115 T	XL	BSW	15503380000	Yes	31.1	35.3	51	(7.0 - 9.0)	2,679	12	669
265/60 R 18	114 T	XL	BSW	15503350000	Yes	30.5	36.6	51	(7.5 - 9.5)	2,601	12	681
265/65 R 18	116 T	XL	BSW	15503360000	Yes	31.6	38.8	51	(7.5 - 9.5)	2,756	12	658
275/65 R 18	116 T	XL	BSW	15503300000	Yes	32.1	38.8	51	(7.5 - 9.5)	2,756	12	648
275/55 R 20	117 T	XL	BSW	15503270000	Yes	31.9	38.3	51	(7.5 - 9.5)	2,833	12	651
275/60 R 20	116 T	XL	BSW	15503320000	Yes	33.0	39.6	51	(7.5 - 9.5)	2,756	12	630

BSW = Black Sidewall

Stud Length for LT-metric sizes: 11 mm (TSMI #12)