

# MAXIMUM™

## 20V max\*

### Cordless Impact Wrench



Model no. 054-3245-2

**IMPORTANT:**

Please read this manual carefully before using this product, and save it for reference.

**INSTRUCTION  
MANUAL**

**TABLE OF CONTENTS**

|                          |    |
|--------------------------|----|
| TECHNICAL SPECIFICATIONS | 4  |
| SAFETY INSTRUCTIONS      | 5  |
| IMPORTANT INFORMATION    | 9  |
| PARTS LIST               | 10 |
| KNOW YOUR TOOL           | 11 |
| OPERATING INSTRUCTIONS   | 12 |
| MAINTENANCE              | 18 |
| WARRANTY                 | 20 |

**NOTE:** If any parts are missing or damaged, or if you have any questions, please call our toll-free helpline at 1-888-670-6682.

**SAVE THESE INSTRUCTIONS**

This manual contains important safety and operating instructions. Read all instructions and follow them with use of this product.

model no. 054-3245-2 | contact us 1-888-670-6682

MAXIMUM™

## TECHNICAL SPECIFICATIONS

|                              |  |
|------------------------------|--|
| MOTOR                        | 18V DC   |
| DRIVE                        | 1/2" square  |
| VARIABLE SPEEDS              | 0-2700 RPM/0-3300 BPM                              |
| MAX. TORQUE                  | 145 ft-lb  |
| ON-BOARD WORK LIGHT          | LED  |
| BATTERY                      | 20V max* (2.0 Ah) lithium-ion                      |
| REPLACEMENT BATTERIES        | 054-3203-2 (2.0 Ah); 054-3206-6(4.0 Ah)            |
| CHARGER                      | 35-minute, diagnostic                              |
| COMPATIBLE MAXIMUM CHARGER   | 054-3204-0   |
| OPTIMUM CHARGING TEMPERATURE | 50 to 86°F (10-30°C)                               |
| DIMENSIONS                   | 6 5/16 x 7 13/32 x 2 11/16"<br>(160 x 188 x 68 mm) |
| WEIGHT                       | 2 lb 5 oz (1.06 kg) without battery                |

\*Maximum battery voltage without workload; with workload nominal voltage is 18V.

## WORK AREA SAFETY

- **Keep work area clean and well lit.** Cluttered or dark areas invite accidents. Rags, clothes, cords, strings and similar items should never be left around the work area.
- **Do not operate power tools in explosive environments, such as in the presence of flammable liquids, gases, or dust.** Power tools create sparks, which may ignite the dust or fumes.
- **Keep children and bystanders away while operating a power tool.** Distractions can cause the operator to lose control.

## ELECTRICAL SAFETY

- **Power tool plugs must match the outlet. Never modify the plug in any way. Do not use any adaptor plugs with grounded power tools.** Unmodified plugs and matching outlets will reduce risk of electric shock.
- **Avoid body contact with grounded surfaces such as pipes, radiators, ranges and refrigerators.** There is an increased risk of electric shock if your body is grounded.
- **Do not expose power tools to rain or wet conditions.** Water entering a power tool will increase the risk of electric shock.
- **Do not abuse the cord. Never use the cord for carrying, pulling or unplugging the power tool. Keep the cord away from heat, oil, sharp edges or moving parts.** Replace damaged cords immediately. Damaged or tangled cords increase the risk of electric shock.
- **When operating a power tool outdoors, use an extension cord suitable for outdoor use.** Use of a cord suitable for outdoor use reduces the risk of electric shock.
- **If operating a power tool in a damp location is unavoidable, use a residual current device (RCD) or ground fault circuit interrupter (GFCI) protected supply.** Use of an RCD or GFCI reduces the risk of electric shock.

## PERSONAL SAFETY

- **Stay alert, watch what you are doing and use common sense when operating a power tool. DO NOT use a power tool while you are tired or under the influence of drugs, alcohol or medication.** A moment of inattention while operating power tools may result in serious personal injury.



## WARNING!

- Before operating this tool, carefully read this instruction manual and all of the labels affixed to the tool. Failure to follow all warnings and instructions may result in electric shock, fire and/or serious injury.
- The term "power tool" in the warnings refers to your mains operated (corded) power tool or battery operated (cordless) power tool.
- Save all warnings and instructions for future reference.

- **Use personal protective equipment. Always wear eye protection.** Protective equipment such as a dust mask, non-skid safety shoes, a hard hat, or hearing protection will reduce personal injuries.
- **Avoid accidental starting.** Ensure the switch is in the “off” position before connecting to a power source and/or battery pack, or picking up or carrying the tool. Carrying power tools with your finger on the switch or plugging in power tools that have the switch on invites accidents.
- **Remove any adjusting key or wrench before turning the power tool on.** A wrench or key left attached to a rotating part of the power tool may result in personal injury.
- **Do not overreach. Keep proper footing and balance at all times.** This enables better control of the power tool in unexpected situations.
- **Dress properly. Do not wear loose clothing or jewellery. Always wear eye and ear protection and use a dust mask. Keep your hair, clothing and gloves away from moving parts.** Loose clothes, jewellery or long hair can be caught in moving parts.
- **If devices are used for dust extraction and collection, ensure these devices are connected and used properly.** Use of dust collection devices can reduce dust-related hazards.
- **Do not use on a ladder or unstable support.** Stable footing on a solid surface allows for better control of the power tool in unexpected situations.

#### POWER TOOL USE AND CARE

- **Do not force the power tool. Use the correct power tool for your application.** The correct power tool will do a better and safer job if used for the function it was designed for.
- **Do not use the power tool if the switch does not turn it on and off.** Any power tool that cannot be controlled with the switch is dangerous and must be repaired.
- **Disconnect the plug from the power source and/or the battery pack from the power tool before making any adjustments, changing accessories, or storing the power tool.** Such preventive safety measures reduce the risk of starting the power tool accidentally.
- **Store idle power tools out of the reach of children and do not allow persons unfamiliar with the power tool or these instructions to operate the power tool.** Power tools are dangerous in the hands of untrained users.
- **Maintain power tools with care. Check for misalignment or binding of moving parts, breakage of parts and any other condition that may affect the power tool's operation. If damaged, have the power tool repaired before use.** Many accidents are caused by poorly maintained power tools.
- **Keep cutting tools sharp and clean.** Properly maintained cutting tools with sharp cutting edges are less likely to bind and are easier to control.
- **Use the power tool, accessories, tool bits, etc., in accordance with these instructions, taking into account the working conditions and the work to be**

**performed.** Use of the power tool for operations different from those intended could result in a hazardous situation.

#### BATTERY TOOL USE AND CARE

- **Ensure the switch is in the “off” position before inserting the battery pack.** Inserting the battery pack into power tools that have the switch “on” invites accidents.
- **When recharging, use only the charger that is specified by the manufacturer.** A charger that is suitable for one type of battery pack may create a risk of fire when used with another battery pack.
- **Use only specifically designated battery packs with power tools.** The use of any other battery pack may create a risk of injury or fire.
- **When the battery pack is not in use, keep it away from objects that can create a connection between the terminals, such as paper clips, coins, keys, nails, screws or other small metal objects.** Short-circuiting the battery terminals may cause burns or a fire.
- **Under abusive conditions, liquid may be ejected from the battery; avoid contact. If contact accidentally occurs, flush with water. If liquid contacts eyes, seek medical help.** Liquid ejected from the battery may cause irritation or burns.

#### SERVICE

- **Have your power tool serviced by a qualified repair person using only identical replacement parts.** This will ensure that the safety of the power tools is maintained.
- **When servicing a tool, use only identical replacement parts.** Follow the instructions in the Maintenance section of this manual. The use of unauthorized parts or failure to follow maintenance instructions may create a risk of electric shock or injury.

#### SPECIFIC SAFETY RULES FOR CORDLESS IMPACT WRENCH

- Do not let comfort or familiarity with product (gained from repeated use) replace strict adherence to impact wrench safety rules. If you use this tool unsafely or incorrectly, you can suffer serious personal injury.
- Hold power tools by insulated gripping surfaces, when performing an operation where the fastener may contact hidden wiring or its own cord. Fasteners contacting a “live” wire may make exposed metal parts of the power tool “live” and could give the operator an electric shock.
- Wear ear protectors.
- Check the socket carefully for wear, cracks or damage before installation.
- Hold the tool firmly.
- Always be sure you have a firm footing. Be sure no one is below when using the tool in high locations.
- The proper fastening torque may differ depending upon the kind or size of the bolt. Check the torque with a torque wrench.

**SAFETY INSTRUCTIONS FOR BATTERY PACK AND CHARGER**

- **If the battery pack casing is cracked or damaged, do not insert into charger.** There is a danger of electric shock or electrocution.
- **Don't allow any liquid to get inside charger.** Electric shock may result. To facilitate cooling of the battery pack after use, avoid placing the charger or battery pack in a warm environment such as in a metal shed, or a trailer that is not insulated.
- **This charger is not intended for any uses other than charging rechargeable batteries.** Any other use may result in risk of fire, electric shock or electrocution.
- **Do not place any object on top of the charger or place the charger on a soft surface that may result in excessive internal heat.** Do not place the charger near any heat source.
- **To reduce the potential risk of damage to the electric plug and cord,** pull by the plug rather than the cord when disconnecting the charger from the power supply.
- **Make sure the cord is located so it will not be stepped on, tripped over, or otherwise subjected to damage or stress.**
- **An extension cord should not be used unless absolutely necessary.** Use of an improper extension cord could result in a risk of fire, electric shock or electrocution.
- **Do not operate the charger if it has received a sharp blow, been dropped or otherwise damaged in any way.**
- **Do not disassemble charger.** Take it to an authorized repair facility when service or repair is required. Incorrect reassembly may result in a risk of electric shock, electrocution or fire.
- **To prevent the risk of electric shock, unplug the charger from the outlet before attempting to clean it.** Only removing the battery pack from the charger will not reduce this risk.
- **DO NOT** store or use the tool and battery pack in locations where the temperature may reach or exceed 122°F (50°C), which can lead to deterioration of the storage battery.
- **The charger is designed to operate on standard household electrical power (120 V AC).** Do not attempt to use it on any other voltage.

**WARNING!**

This manual contains important safety and operating instructions for your battery and charger. Before using the charger, read all instructions and warnings on the charger, the battery pack and the tool.

**ADDITIONAL INFORMATION ON BATTERY AND CHARGER**

- The battery pack is not fully charged out of the carton. First read the safety instructions and then follow the charging notes and procedures.
- The longest life and best performance can be obtained if the battery pack is charged when the air temperature is 59-77°F (15-25°C). Do not charge the battery pack where the air temperature is below 32°F (0°C) or above 113°F (45°C). This is important and will prevent damage to the battery pack.
- Do not incinerate the battery pack even if it is seriously damaged or is completely worn out. The battery can explode in a fire.
- Never attempt to open the battery pack for any reason. If the plastic housing of the battery pack breaks or cracks, immediately discontinue use and do not recharge.
- The length of service from your battery will depend on the type of work you are doing. The battery has been designed to provide maximum trouble-free life. However, like all batteries, it will eventually wear out.
- To obtain the longest possible battery life, we suggest the following:
  - Store and charge your battery in a cool area. Temperatures above or below normal room temperature will shorten battery life.
  - Never store the battery in a discharged condition. Recharge it immediately after it has been discharged.
- All batteries gradually lose their charge. The higher the temperature, the quicker they lose their charge. If you store your tool for long periods of time without use, recharge the battery every month or two. This practice will prolong battery life.

**BATTERY PACK REMOVAL AND PREPARATION FOR RECYCLING**

To preserve natural resources, please recycle or dispose of batteries properly. This product contains a lithium-ion battery. Local, provincial or federal laws may prohibit disposal of lithium-ion batteries in ordinary trash. Consult your local waste authority for information regarding available recycling and/or disposal options.

**WARNING!**

Upon removal, cover the battery pack's terminals with heavy-duty adhesive tape. Do not attempt to destroy or disassemble.




| No. | Description |
|-----|-------------|
|-----|-------------|


- |   |                           |
|---|---------------------------|
| 1 | 1/2" square anvil         |
| 2 | LED worklight             |
| 3 | Forward & reverse lever   |
| 4 | Trigger switch            |
| 5 | Remaining power indicator |

| No. | Description |
|-----|-------------|
|-----|-------------|

- |    |                           |
|----|---------------------------|
| 6  | Battery release button    |
| 7  | Rechargeable battery pack |
| 8  | Charger                   |
| 9  | Charging indicator        |
| 10 | Detachable cable & plug   |

**WARNING!**

- Remove the product and any accessories from the package. Inspect the tool carefully to make sure no breakage or damage occurred during shipping.
- Do not discard the carton or any packaging material until all parts have been examined.



| NO. | DESCRIPTION |
|-----|-------------|
|-----|-------------|


- |   |               |
|---|---------------|
| 1 | RIGHT HOUSING |
| 2 | SCREW         |
| 3 | BUMPER        |
| 4 | SCREW         |
| 5 | GEAR BOX ASSY |
| 6 | SCREW         |
| 7 | MOTOR         |
| 8 | REAR COVER    |
| 9 | LED COVER     |

| NO. | DESCRIPTION |
|-----|-------------|
|-----|-------------|

- |    |                         |
|----|-------------------------|
| 10 | FORWARD & REVERSE LEVER |
| 11 | LED LABEL               |
| 12 | POWER INDICATOR COVER   |
| 13 | SWITCH & PCB ASSEMBLY   |
| 14 | LEFT HOUSING            |
| 15 | NUT                     |
| 16 | BATTERY PACK            |
| 17 | CHARGER                 |
| 18 | DETACHABLE CABLE & PLUG |

**FITTING AND REMOVING THE BATTERY PACK TO THE IMPACT WRENCH**

- To install the battery pack to the tool, align the raised portion of the battery pack with the grooves on the bottom of the tool, and slide it firmly into the handle until you hear the lock snap into place. (Fig. A)
- To remove the battery pack from the tool, press the battery pack release button and slide the battery pack completely out of tool handle.




(Fig. A)

**CHARGING PROCEDURE**

- Connect the plug cable to the charger, and then plug into an appropriate outlet before inserting battery pack (Fig. B). All three charging lights will be on for two seconds and then off.
- Insert the battery pack into the charger, making sure the pack is fully seated in the charger (Fig. C). During the charging process, the charging lights will indicate the charging status as follows:
  - Less than 30% charged: all three charging lights will blink in sequence.
  - Less than 60% charged: one light will stay on, while the

other two lights will blink in sequence.

- Over 60% charged: two lights will stay on, while the remaining light will blink continuously.
- Fully charged: all three lights will remain on continuously.
- The charging process will last approximately 35 minutes and continuous lighting of all three charging lights will indicate charging is complete.




(Fig. B)

**CHARGER DIAGNOSTICS**

The charger is designed to detect certain problems that can arise with battery packs

- When the charger detects the battery pack is overheated, all three charging lights will blink at the same time. Please remove the battery and allow it to cool down for 15-30 minutes and re-insert.
- When the charger detects a malfunction in the battery, two charging lights will blink at the same time. Please remove the battery and allow it to cool down for 15-30 minutes. Then re-insert the battery pack into the charger. If two charging lights still flash, the battery may require service.
- When the charger detects a malfunction of the charger itself, three charging lights will blink at the same time. Please remove the battery pack and unplug the charger for at least 2 minutes. After 2 minutes, plug charger back in and re-insert the pack into the charger. If all three charging lights still blink at the same time, the charger may require service.



(Fig. C)

**ON/OFF TRIGGER SWITCH**

To turn the tool on, squeeze the trigger switch. To turn the tool off, release the trigger switch.

**WARNING!**

- Do not allow familiarity with tools to make you careless. Remember that a careless fraction of a second is enough to cause serve injury.
- Before attempting to use this cordless tool, become familiar with all of its operating features and safety requirements.
- To reduce the risk of serious personal injury, turn tool off and disconnect battery pack before making any adjustments or removing/installing attachments or accessories.

**CAUTION!**

- Before attempting to charge the battery, check the charger and the battery to ensure the charging equipment matches the battery supplied. The components are all labeled with component numbers.
- The rechargeable battery is not fully charged on leaving the factory. Charge the rechargeable battery before first use.
- Recharge discharged batteries as soon as possible after use or battery life may be greatly diminished. For longest battery life, do not discharge batteries fully.

**CAUTION!**

The working temperature of the charger is 32 to 113°F (0 to 45°C).

**NOTE:** Charging times may be longer depending on the surrounding temperature and battery condition.

**VARIABLE SPEED**


The variable speed trigger switch delivers higher speed with increased trigger pressure and lower speed with decreased trigger pressure.

**FORWARD AND REVERSE**

The direction of bit rotation is reversible and is controlled by a selector located above the trigger switch. (Fig. D)

With the impact wrench held in normal operating positions:

- Position the forward/reverse selector to the left of the tool for forward.
- Position the forward/reverse selector to the right of the tool for reverse.
- Position the forward/reverse selector in the centre will lock the switch trigger to help reduce the possibility of accidental starting when not in use.




(Fig. D)

**INSTALLING AND REMOVING A SOCKET**

Always use the correct size socket for bolts and nuts. An incorrect size socket will result in inaccurate and inconsistent fastening torque and/or damage to the bolt or nut.

To install the socket, push it onto the anvil of the tool until it locks into place. (Fig. E) To remove the socket, simply pull it off.



(Fig. E)

**NOTE:** This tool is equipped with an electric brake. When the brake is functioning properly, sparks may be visible through the vent slots in the housing. This is normal and is the action of the brake.

**NOTE:** The impact wrench will not run unless the direction of forward/reverse selector is engaged fully to the left or right.

**CAUTION!**

To prevent gear damage, always allow the chuck to come to a complete stop before changing the direction of rotation.

**LED WORKLIGHT**

When the unit is switched on, the LED worklight also comes on to ensure better vision and to make working in dark areas safer. LED work light remains on for 15 seconds after the trigger switch is released.

**REMAINING POWER INDICATOR**

If the trigger switch is pressed, the remaining power indicator lights for 5 seconds and the battery's remaining power can be checked.


| LED INDICATOR |  | REMAINING POWER STATUS |
|---------------|--|------------------------|
| 1             |  | 0-25 %                 |
| 2             |  | 25-50 %                |
| 3             |  | 50-75 %                |
| 4             |  | 75-100 %               |

**BELT HOOK**

The belt hook is used to hang the tool from your waist belt while working. Install the belt hook securely in the groove of the drill and tighten the screw to fix the hook firmly. (Fig. F)

**TEMPERATURE CUT OUT**

When used as intended, the driver cannot be subject to overload. But running continuously at full load for a long time will cause the battery pack to overheat. If the allowable battery temperature range of 32-158°F (0-70°C) is exceeded, the battery pack will automatically stop operating and will not restart until it has cooled to a safe level.



(Fig. F)

**WARNING!**

Do not insert or remove socket while the tool is activated. Make sure the battery pack is removed or the forward & reverse lever is in the centre locking position when inserting or removing socket.

**CAUTION!**

- When using the belt hook, hang the power tool firmly so as not to drop it accidentally. If the power tool is dropped, it may lead to an accident.
- When carrying the tool hooked to your waist belt, do not fit any bit to the top of the power tool, as this may lead to accidental injury.



**LOW-VOLTAGE CUT-OUT**

The battery pack used on this tool is fitted with a low-voltage cut-out feature within the circuitry. The low-voltage cut-out feature operates when the voltage drops below a pre-set value. This feature automatically stops the tool from operating. When this condition occurs you will need to either insert another battery pack into the tool or recharge the existing battery pack.

**TIGHTENING FASTENERS**

Before starting your job, always perform a test operation to determine the proper fastening time for your bolt or nut.

- Install the socket on the anvil. Then, set the forward & reverse lever for the suitable setting (forward or reverse).
- Hold the tool firmly and place the socket in line with the bolt or nut.
- Press the trigger switch to turn on the impact wrench. The variable speed trigger switch delivers higher speed with increased trigger pressure and lower speed with decreased trigger pressure.
- Fasten the bolt or nut to the proper torque.
- To turn the impact wrench off, release the trigger switch.
- After fastening, always check the torque with a torque wrench.

Practice with various fasteners, noting the length of time required to reach the desired torque. Check the tightness with a torque wrench. If the fasteners are too tight, reduce the impacting time. If they are not tight enough, increase the impacting time.

The fastening torque is affected by a wide variety of factors, including the following:

- Socket. Failure to use the correct size socket will cause a reduction in the fastening torque. A worn socket (wear on the hex end or square end) will cause a reduction in the fastening torque.

**NOTE:**

- The impact wrench will not restart until the battery pack has cooled.
- Do not force cool the pack in any way. Do not place in refrigerator or freezer. To reduce the temperature of the cells remove the battery pack from the tool and place the battery pack in a free air environment, out of direct sunlight or any other heat source.

**NOTE:** Attempting to restart the tool without either recharging the battery or installing another battery (with charge) will lead to tool restarting and then stopping again, after only a few seconds of operation.

- Bolt. The proper fastening torque will differ according to the diameter of the bolt, the torque coefficient, the bolt length, and the class of bolt.
- The use of a universal joint or an extension bar (both available separately) will reduce the fastening force of the impact wrench somewhat. Compensate by fastening for a longer period of time.
- The manner of holding the tool or the material to be fastened will affect the torque.

**LOOSENING FASTENERS**

- With the proper impact socket securely mounted to the cordless impact wrench, slide the impact socket on to the bolt head.
- Verify that the rotational direction is “reverse”.
- Hold the tool securely with both hands and squeeze the trigger switch. The tool will start to impact immediately.
- Once the fastener has “broken loose” it will start to unthread. Be careful that you do not allow a fastener to spin freely once it is no longer engaged with the other threaded part, as it may be thrown out of the socket.

**NOTE:**

- Hold the tool straight along the axis of the bolt or nut.
- Excessive fastening torque may damage the bolt/nut or socket.

**NOTE:**

The torque that is required to loosen a fastener averages 75% to 80% of the tightening torque, depending on the condition of the contacting surfaces. However, if rust or corrosion causes seizing, more torque may be required.

**GENERAL MAINTENANCE**

Avoid using solvents when cleaning plastic parts. Most plastics are susceptible to damage from various types of commercial solvents and may be damaged by their use. Use clean cloths to remove dirt, dust, oil, grease, etc.

**BATTERIES**

The battery pack is equipped with lithium-ion rechargeable batteries. The duration of use from each charge will depend on the type of work performed.

The batteries in this tool have been designed to provide maximum trouble-free life. Like all batteries, they will eventually wear out. Do not disassemble the battery pack or attempt to replace the batteries. Handling of the batteries, especially when wearing rings and jewellery, could result in a serious burn.

To obtain the longest possible battery life, read and understand the operator's manual.

- It is good practice to unplug the charger/adaptor and remove the lithium-ion battery pack when not in use.

**FOR LITHIUM-ION BATTERY PACK STORAGE LONGER THAN 30 DAYS:**

- Store the lithium-ion battery pack where the temperature is below 79°F (26°C) and free of moisture.
- Store lithium-ion battery packs in a 30-50% charged condition.
- Every six months of storage, fully charge the lithium-ion battery pack.
- Exterior may be cleaned with a cloth or soft non-metallic brush.

**WARNING!**

- To avoid serious personal injury, always remove the battery pack from the tool when cleaning or performing any maintenance.
- When servicing, use only identical replacement parts. Use of any other parts may create a hazard or cause product damage. To ensure safety and reliability, all repairs should be performed by a qualified service technician.
- It is not recommended to use compressed dry air to clean the driver. If cleaning with compressed air is the only method available, always wear safety goggles or safety glasses with side shields when using compressed air to clean the tool. If the operation is dusty, also wear a dust mask.
- Do not at any time let brake fluids, gasoline, petroleum-based products, penetrating oils, etc. to come in contact with plastic parts. Chemicals can damage, weaken or destroy plastic which may result in serious personal injury.

**BATTERY PACK REMOVAL AND PREPARATION FOR RECYCLING**

To preserve natural resources, please recycle or dispose of batteries properly. This product contains lithium-ion batteries. Local, provincial, or federal laws may prohibit disposal of lithium-ion batteries in ordinary trash. Consult your local waste authority for information regarding available recycling and/or disposal options.

**WASTE DISPOSAL**

The product must not be discarded with normal household waste. It must be disposed of properly.


**WARNING!**

Upon removal of the battery pack for disposal or recycling, cover the battery pack's terminals with heavy-duty adhesive tape. Do not attempt to destroy or disassemble the battery pack or remove any of its components. Lithium-ion batteries must be recycled or disposed of properly. Also, never touch the terminals with metal objects and/or body parts as a short circuit may result. Keep away from children. Failure to comply with these warnings could result in fire and/or serious injury.

**5-YEAR LIMITED WARRANTY**

This MAXIMUM product is guaranteed for a period of 5 years from the date of original retail purchase against defects in workmanship and materials only and is subject to the following components:

- a) Component A: The carrying case is guaranteed for a period of 1-year from the date of original retail purchase against defects in workmanship and materials.
- b) Component B: Accessories, including drill bits and saw blades, do not carry a warranty.



Subject to the conditions and limitations described below, this product, if returned to us with proof of purchase within the stated warranty period and if covered under this warranty, will be repaired or replaced (with the same model, or one of equal value or specification), at the sole discretion of the Maximum Canada authorized repair centre ("Service Provider"). We will bear the cost of any repair or replacement and any costs of labour relating thereto.

**These warranties are subject to the following conditions and limitations:**

- a) a bill of sale verifying the purchase and purchase date must be provided;
- b) defects in workmanship and material to be assessed and determined by the Service Provider
- c) this warranty will not apply to any product or part thereof which is worn or broken or which has become inoperative due to abuse, misuse, accidental damage, neglect or lack of proper installation, operation or maintenance (as outlined in the applicable owner's manual or operating instructions);
- d) this warranty does not apply to normal wear and tear or to expendable parts or accessories (including drill bits and saw blades) that may be supplied with the product that by their nature have a limited life span and are expected to become inoperative or unusable after a reasonable period of use;
- e) this warranty will not apply to routine maintenance and consumable items such as, but not limited to, fuel, lubricants, vacuum bags, blades, belts, sandpaper, bits, fluids, rubber o-rings, tune-ups or adjustments;
- f) this warranty excludes the following components that may accompany your product:
  - (1) The carrying case, which is only for a period of 1-year from the date of original retail purchase against defects in workmanship and materials.
  - (2) Accessories, including drill bits and saw blades, which do not carry a warranty of any kind.
- g) this warranty will not apply where damage is caused by repairs made or attempted by anyone other than the Service Provider (i.e. persons not authorized by the manufacturer), and any such unauthorized repairs or attempted repairs shall void this warranty in its entirety;
- h) this warranty will not apply to any parts other than original parts, except to the extent that the retailer or manufacturer or persons authorized by either of them have repaired or replaced them;

- i) this warranty will not apply to any product that was sold to the original purchaser as a reconditioned or refurbished product (unless otherwise specified in writing);
- j) this warranty will not apply to any product or part thereof if any part from another manufacturer is installed therein or any repairs or alterations have been made or attempted by unauthorized persons;
- k) this warranty will not apply to normal deterioration of the exterior finish, such as, but not limited to, scratches, dents, paint chips, or to any corrosion or discolouring by heat, abrasive and chemical cleaners; and
- l) this warranty will not apply to component parts sold by and identified as the product of another company, which shall be covered under that product manufacturer's warranty, if any;
- m) any products replaced by the retailer in attempt to fulfill warranty obligations is subject to the original product warranty conditions and related time period as initiated by the original date of purchase; if product is purchased in Quebec, the warranty term will be extended for a period equal to the time during which the Quebec retailer possesses the product in attempt to fulfill warranty obligations; replaced product will not default to new product warranty conditions; and
- n) The retailer and manufacturer's sole obligation and the purchaser's sole remedy under this warranty shall be as set out herein. The warranties contained herein are not transferable and are given only to the purchaser. FURTHER, THE WARRANTIES SET OUT HEREIN ARE IN LIEU OF ALL OTHER WARRANTIES OR CONDITIONS, WHETHER EXPRESS, IMPLIED OR STATUTORY (INCLUDING SUCH AS ARISE UNDER THE SALE OF GOODS ACT OR THE INTERNATIONAL SALE OF GOODS ACT), ARISING OUT OF A COURSE OF DEALING OR USAGE OF TRADE OR OTHERWISE, INCLUDING, SUBJECT TO APPLICABLE LAW, ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY, MERCHANTABILITY, QUALITY, FITNESS OR ADEQUACY FOR A PARTICULAR PURPOSE OR USE, AND ALL OTHER SUCH WARRANTIES ARE EXPRESSLY DISCLAIMED BY THE RETAILER AND MANUFACTURER.

**ADDITIONAL LIMITATIONS**

This warranty applies only to the original purchaser and may not be transferred.

This warranty applies for a period of 5 years from the date of original retail purchase, as indicated on the bill of sale.

Neither the retailer, Maximum Canada, nor the manufacturer shall be liable for any other expense, loss or damage, including, without limitation, any indirect, incidental, consequential or exemplary damages arising in connection with the sale, use or inability to use this product.

Under no circumstances shall the retailer, Maximum Canada, or manufacturer be liable to the purchaser for any claim for (a) indirect, special, punitive, incidental, exemplary, or consequential damages, (b) compensation for loss of profits, anticipated revenue, savings or goodwill, or other economic loss of the purchaser, (c) exemplary, aggravated or punitive damages howsoever incurred, (d) contribution or set-off in respect of any claims against the purchaser, (e) any damages whatsoever relating to third party products or services or the purchaser's materials, or (f) any damages

whatsoever relating to interruption, delays, errors or omissions; in each case under any theory of law or equity, arising out of or in any way related to this warranty, even if advised of the possibility thereof. Notwithstanding any provision herein or entitlement of the purchaser at law, in equity or otherwise, in no event shall the liability of the retailer or manufacturer under this warranty, whether in contract, tort, product liability or otherwise, exceed, in the aggregate, the amount paid by the purchaser to the retailer for the product to which this warranty applies.

#### NOTICE TO CONSUMER

This warranty gives you specific legal rights, and you may have other rights, which may vary from province to province. The provisions contained in this warranty are not intended to limit, modify, take away from, disclaim or exclude any statutory warranties set forth in any applicable provincial or federal legislation.

In addition to the 5-Year Limited Warranty, this MAXIMUM product is covered by our:

#### 3-YEAR BATTERY/CHARGER REPAIR WARRANTY

Maximum Canada will repair or replace the batteries/chargers which have worn beyond reasonable use due to normal use of such items, for a period of three (3) years from the date of original purchase.

Any defects with such battery and/or charger will be subject to repair or replacement as determined by the Service Provider. For proper servicing, both the battery and charger will require diagnosis to evaluate warranty requirements and therefore must both be provided to the Service Provider at the time of service request.

The following is excluded from this 3-Year Battery/Charger Repair Warranty:

- a) Damages that are a result of abuse or misuse
- b) Any wear and tear that does not affect the core function of the product.

#### 1-YEAR REPAIR WARRANTY

Maximum Canada will maintain this product and replace critical parts which have worn beyond reasonable use through normal use of such product, any time during the first year after purchase.

The following are excluded from this 1-Year Repair Warranty:

- a) Missing or damaged parts or components that are a result of abuse or misuse;
- b) Any wear and tear to non-critical parts or accessories that do not affect the core function of the product.

#### 90-DAY SATISFACTION GUARANTEE

If you are not completely satisfied with the performance of your MAXIMUM product for any reason, you can return it within 90 days from the date of purchase with proof of purchase for exchange or a full refund.

Made in China

Imported by MAXIMUM Canada Toronto, Canada M4S 2B8