



SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	MotoMaster 2-Stroke Semi-Synthetic Powersports Oil
Other means of identification	Not available
Recommended use	Multi Use 2 Stroke Motor Oil
Recommended restrictions	None known.
Manufacturer information	Irving Blending & Packaging PO Box 1169 Saint John, NB E2L 4E6 CA Phone: 1.800.574.5823 Emergency Phone: 1.800.424.9300 (CHEMTREC)
Supplier	See above.

2. Hazards Identification

Physical hazards	Not classified.	
Health hazards	Sensitization, skin	Category 1
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	

Label elements



Signal word	Warning
Hazard statement	May cause an allergic skin reaction.
Precautionary statement	

Prevention	Avoid breathing mist or vapor. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.
Response	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse.
Storage	Store away from incompatible materials.
Disposal	Dispose of container in accordance with local, regional, national and international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)

None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)

None known

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
2H-1-Benzopyran-2-one		91-64-5	0.1-1*
Distillates (petroleum), light hydrotreated		64742-47-8	15-30*
Nonane		111-84-2	1-5*
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy		64742-70-7	30-60*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

5. Fire Fighting Measures

Suitable extinguishing media	Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Cool containers exposed to heat with water spray and remove container, if no risk is involved.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep out of low areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling	Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas.
Conditions for safe storage, including any incompatibilities	Keep away from heat and sources of ignition. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Vapor.
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	
		100 ppm	
Nonane (CAS 111-84-2)	TWA	1050 mg/m3	
		200 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Nonane (CAS 111-84-2)	TWA	200 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Nonane (CAS 111-84-2)	TWA	200 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Nonane (CAS 111-84-2)	TWA	200 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	1590 mg/m3	
		400 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	
		100 ppm	
Nonane (CAS 111-84-2)	TWA	1050 mg/m3	
		200 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	PEL	400 mg/m3	
		100 ppm	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Nonane (CAS 111-84-2)	TWA	200 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	100 mg/m3	
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3	
		100 ppm	
Nonane (CAS 111-84-2)	TWA	1050 mg/m3	
		200 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**Canada - Alberta OELs: Skin designation**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Toluene (CAS 108-88-3)

Can be absorbed through the skin.
Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Toluene (CAS 108-88-3)

Can be absorbed through the skin.
Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical goggles are recommended.

Skin protection**Hand protection**

Wear protective gloves.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Blue
Odor	Vanilla
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-40 °F (-40 °C)
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	210.2 °F (99.0 °C) Pensky-Martens Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.8731 @ 15°C
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	8.4 cSt @ 100°C 53.9 cSt @ 40°C

10. Stability and Reactivity

Reactivity	Strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.

Conditions to avoid	Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause sensitization by skin contact.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2H-1-Benzopyran-2-one (CAS 91-64-5)		
Acute		
<i>Dermal</i>		
LD50	Rat	293 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Rat	293 mg/kg, ECHA
<i>Oral</i>		
LD50	Guinea pig	202 mg/kg, HSDB
	Mouse	196 mg/kg, HSDB
	Rat	> 320 mg/kg, ECHA
		680 mg/kg, ECHA
		520 mg/kg, ECHA
		293 mg/kg, ECHA
		290 mg/kg, ECHA
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 4000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Cat	> 6.4 mg/L, 6 Hours, ECHA
	Rat	> 7.5 mg/L, 6 Hours, ECHA
		> 6 mg/L, 4 Hours, ECHA
		> 5.7 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.2 mg/L, 4 Hours, ECHA
		> 4.6 mg/L, 4 Hours, ECHA
		> 4.5 mg/L, 4 Hours, ECHA
		> 4.3 mg/L, 4 Hours, ECHA
		> 0.1 mg/L, 8 Hours, ECHA
		5.2 mg/l/4h, LOLI
<i>Oral</i>		
LD50	Rat	> 20000 mg/kg, ECHA

Components	Species	Test Results
Nonane (CAS 111-84-2)		> 25 ml/kg, HSDB
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	3200 ppm, 4 Hours, HSDB 23.8 mg/L, 8 Hours, ECHA 17 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA > 5.5 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA > 2000 mg/kg, ECHA 5000 mg/kg, ECHA
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	May cause sensitization by skin contact.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.	
	Contains < 3% (w/w) DMSO-extract	
ACGIH Carcinogens		
Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	A2 Suspected human carcinogen.	
Canada - Manitoba OELs: carcinogenicity		
ETHYL BENZENE (CAS 100-41-4)	Confirmed animal carcinogen with unknown relevance to humans.	
MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, POORLY AND MILDLY REFINED (CAS 64742-70-7)	Suspected human carcinogen.	

IARC Monographs. Overall Evaluation of Carcinogenicity

2H-1-Benzopyran-2-one (CAS 91-64-5)

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

Volume 77 - 3 Not classifiable as to carcinogenicity to humans.

Volume 101 - 2B Possibly carcinogenic to humans.

Volume 77 - 2B Possibly carcinogenic to humans.

Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.

Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

US NTP Report on Carcinogens: Anticipated carcinogen

Cumene (CAS 98-82-8)

Reasonably Anticipated to be a Human Carcinogen.

US NTP Report on Carcinogens: Known carcinogen

Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Teratogenicity	Not available.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological Information

Ecotoxicity	See below		
Ecotoxicological data Components		Species	Test Results
2H-1-Benzopyran-2-one (CAS 91-64-5)			
Aquatic			
Fish	LC50	Guppy (Poecilia reticulata)	32 - 100 mg/L, 96 hours
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2.9 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
General	Marine Pollutants Exemption. 1.45.1. : Part 3, Documentation, and Part 4, Dangerous Goods Safety Marks, do not apply to substances that are classified as marine pollutants in accordance with section 2.43 of Part 2, Classification, if they are in transport solely on land by road vehicle or railway vehicle. However, substances may be identified as marine pollutants on a shipping document and the required dangerous goods safety marks may be displayed when they are in transport by road or railway vehicle. (SOR/2008-34, s. 23) CFR 171.4: The requirements of this subchapter specific to marine pollutants does not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft, except when all or part of the transportation is by vessel.
U.S. Department of Transportation (DOT)	
Not regulated as dangerous goods.	
Transportation of Dangerous Goods (TDG - Canada)	
Not regulated as dangerous goods.	

15. Regulatory Information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.
Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	1 TONNES
Nonane (CAS 111-84-2)	1 TONNES
Toluene (CAS 108-88-3)	1 TONNES
Xylene (CAS 1330-20-7)	1 TONNES
Export Control List (CEPA 1999, Schedule 3)	
Not listed.	
Greenhouse Gases	
Not listed.	
Precursor Control Regulations	
Toluene (CAS 108-88-3)	Class B
WHMIS 2015 Exemptions	Not applicable
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	
Nonane (CAS 111-84-2)	1.0 % One-Time Export Notification only.
CERCLA Hazardous Substance List (40 CFR 302.4)	
Cumene (CAS 98-82-8)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Nonane (CAS 111-84-2)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
SARA 302 Extremely hazardous substance	No
SARA 311/312 Hazardous chemical	No
SARA 313 (TRI reporting)	
Not regulated.	
Other federal regulations	
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	
Cumene (CAS 98-82-8)	
Ethylbenzene (CAS 100-41-4)	

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

2H-1-Benzopyran-2-one (CAS 91-64-5) Listed.

Cumene (CAS 98-82-8) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

Nonane (CAS 111-84-2) Listed.

Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.

Toluene (CAS 108-88-3) Listed.

Xylene (CAS 1330-20-7) Listed.

US - Illinois Chemical Safety Act: Listed substance

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Nonane (CAS 111-84-2)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US - Louisiana Spill Reporting: Listed substance

Cumene (CAS 98-82-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

Nonane (CAS 111-84-2) Listed.

Toluene (CAS 108-88-3) Listed.

Xylene (CAS 1330-20-7) Listed.

US - Michigan Critical Materials Register: Parameter number

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US - Minnesota Haz Subs: Listed substance

Cumene (CAS 98-82-8) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.

Toluene (CAS 108-88-3) Listed.

Xylene (CAS 1330-20-7) Listed.

US - New Jersey RTK - Substances: Listed substance

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Nonane (CAS 111-84-2)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US - North Carolina Toxic Air Pollutants: Listed substance

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US - Texas Effects Screening Levels: Listed substance

2H-1-Benzopyran-2-one (CAS 91-64-5) Listed.

Cumene (CAS 98-82-8) Listed.

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.

Ethylbenzene (CAS 100-41-4) Listed.

Nonane (CAS 111-84-2) Listed.

Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.

Toluene (CAS 108-88-3) Listed.

Xylene (CAS 1330-20-7) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List

Cumene (CAS 98-82-8)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Ethylbenzene (CAS 100-41-4)

Nonane (CAS 111-84-2)
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Cumene (CAS 98-82-8)
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Ethylbenzene (CAS 100-41-4)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Cumene (CAS 98-82-8)
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)
Ethylbenzene (CAS 100-41-4)
Nonane (CAS 111-84-2)
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Nonane (CAS 111-84-2)
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. California Proposition 65



WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8)	Listed: April 6, 2010
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)	Listed: January 1, 1991
------------------------	-------------------------

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

16-August-2019

Version #

04

Effective date

16-August-2019

Prepared by

Irving Blending & Packaging Phone: 1.800.574.5823

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.